

22/2 (7/0.24) Riser CMR/CL2R

Security and Control



2202UCMRBG - Security CABLE 22/2 (7/0.24) CMR/CL2R 1000' GRAY PULL BOX

Content of the Data Sheet			
Part number	2202UCMRBG		
Voltage	300V		
Test Standard	UL444/UL13		
Conductor	Material	Stranded Bare copper	
	Nom.O.D.(mm)	7/0.24	0.72mm
Insulation	Material	PVC	
	Diameter	1.1±0.05 mm	
shielding	-----		
Sheath	Thickness	0.45±0.05mm	
	External O.D.	3.1+/-0.2 mm	
	Surface	Wavy	
	Material	FR- PVC(complies RoHS)	
	Color	Gray	
Surface Printing	Letter height	2.5±0.3mm	
	Color	BLACK	
	Print error & Space	≤±0.5%, 1m	
Core Color	1. Black, 2.Red		
Packing	1000FT/PULL BOX		
Weight	10.15 lbs/BOX		
Packing length	500ft±4ft		
Rip-cord	Yes	Drain wire	No
Sheath Physical Properties	Before Aging Tensile Strength (Mpa)	≥10.0	
	Elongation(%)	≥100	
	Aging Period (°C × hrs)	100°C × 24h × 7d	
	After Aging Elongation(%)	≥75	
Electrical Characteristics (20°C)	Capacitance	190pf/m	

DC Resistance (Ω/km) max	DC Resistance (Ω/km) max	75	
	Spark test	2.0kv	
	Dielectric Test	1.5kv/min	
Temperature Range:	-20°C to + 75°C		

