

RG11 CMR COAXIAL CABLE
PART NO. 11CCSCMRRB 60% AL BRAID
DESCRIPTION:
**RG11 CMR COAXIAL 1000 FEET BLACK
WOODEN REEL**
Category: RG11 CMR
Test Standard: ETL
PERFORMANCE

Frequency (MHz)	ATT (dB)
55	0.96
211	1.90
300	2.25
400	2.60
550	3.05
750	3.65
870	4.00
1000	4.36
1350	4.98
1750	6.00
2150	6.70
2600	7.63
3000	8.24

STANDARD PACKAGE

Packing	Wooden Reel
Weight	61.73 lbs
Packing Length	1000 ft

CONSTRUCTION DETAILS

Conductor	Material	Solid copper clad steel		
	Nom. O.D. (mm)	1.63	up	+0.01
			down	-0.01
Insulation	Material	Foam PE		
	Diameter	7.11± 0.15 mm		
First Shield	Material	Aluminum/PET-Foil-Bonded		
Second Shield	Material	Aluminum Wire		
	Construction	0.15mm×16×16		
Sheath	Nom. Thickness	1.0mm		
	External O.D	10.00±0.20mm		
	Material	PVC(complies RoHS		
	Color	BLACK		
Sheath Physical Properties	Before Aging Tensile Strength (Mpa)	≥13.8		
	Elongation(%)	≥180		
Electrical Characteristics (20°C)	Nom. Centre Conductor DC Resistance	13.0 ohm/kft		
	Velocity of Propagation (%)	85%		
	Nominal Capacitance	15.6 pF/ft		
	Impedance	75±3 Ohms		
	Jacket Spark Test Voltage	AC 3000V		
Temperature Range	-20°C to +70°C			

Toll Free: (866) 945-5051
 Local: (770) 945-5051
 Fax: (770) 945-9582
www.commoditycables.com

