



www.commoditycables.com

PART NO. 1402SCMRRG



### Description

14 AWG stranded bare copper 2 conductor riser rated Grey jacket

### Features and Benefits

#### RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us. Footage marked descending.

### Suitable Application

- Security Systems
- Sound/Audio System
- Intercom Systems
- Power-Limited Controls

### Standards

NEC Articles: 725, 760, 800  
22-16 AWG: CMR, CL2R, CL3R, FPLR  
14-12 AWG: CL3R, FPLR

### Applicable Standards

UL Type	CL2R, CL3R, FPLR
ROHS Compliant	Yes

### Electricals

Voltage Rating	300 Volts
Conductors	ASTM B-3, B-8
Temperature Rating	-4°C to 75°C
Capacitance	22.5 pF/ft

### Print Legend

COMMODITY CABLES, INC. 14 AWG 2C (UL) TYPE CL2R, CL3R OR FPLR E498766 A1001. Made in USA

Toll Free: (866) 945-5051  
Local: (770) 945-5051  
Fax: (770) 945-9582  
[www.commoditycables.com](http://www.commoditycables.com)

### Construction Details

Total Number Conductors	2
AWG	14
Stranding	19 Strand
Conductor Material	Bare copper
Insulation Material	PVC
Insulation Thickness	.012"
Nominal Insulation Diameter	.098"
Color Code	Red/Gray
Tape Material	Aluminium Mylar
Cabling Overall Lay	4" left hand lay
Final Jacket Material	PVC
Nominal Thickness	.015"
Jacket Color	White
Nominal Jacket Diameter	.238"
Ripcord	Yes

### Print (Surface Print)

Inkjet	Yes
Sequential Foot Marks	Yes

### Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



\*All values in this specification are nominal and are subject to tolerances of +/- 10 to 15%. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice\*