



www.commoditycables.com

PART NO. 1402UCMPRW



Description

14 AWG stranded bare copper 2 conductor Plenum

Features and Benefits

RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us. Footage marked descending.

Suitable Application

- Security Systems
- Sound/Audio System
- Intercom Systems
- Power-Limited Controls

Standards

- NEC Articles: 725, 760, 800
- 22-16 AWG: CMP, CL2P, CL3P, FPLP
- 14-12 AWG: CL3P, FPLP

Applicable Standards

UL Type	CL2P, CL3P, FPLP
ROHS Compliant	Yes

Electricals

Voltage Rating	300 Volts
Conductors	ASTM B-3, B-8
Temperature Rating	-4°C to 75°C
Capacitance	22.5 pF/ft

Print Legend

COMMODITY CABLES, INC. 14 AWG 2C (UL) TYPE CL2P, CL3P OR FPLP E498766 A1001. Made in USA

Toll Free: (866) 945-5051

Local: (770) 945-5051

Fax: (770) 945-9582

www.commoditycables.com

Construction Details

Total Number Conductors	2
AWG	14
Stranding	19 Strand
Conductor Material	Bare copper
Insulation Material	Low smoke copolymer
Insulation Thickness	.012"
Nominal Insulation Diameter	.098"
Color Code	Black/Red
Cabling Overall Lay	4" left hand lay
Final Jacket Material	Low smoke copolymer
Nominal Thickness	.015"
Jacket Color	White
Nominal Jacket Diameter	.225"
Ripcord	Yes

Print (Surface Print)

Inkjet	Yes
Sequential Foot Marks	Yes

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



All values in this specification are nominal and are subjective to tolerances of +/- 10 to 15%. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice