



www.commoditycables.com

PART NO. 1803SCMPRG



Description

18 AWG 3 conductor Shielded Plenum with white jacket

Features and Benefits

RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us. Footage marked descending.

Suitable Application

- Security Systems
- Sound/Audio System
- Intercom Systems
- Power-Limited Controls

Standards

NEC Articles

22-16 AWG: FPLP/760, CMP/800, CL3P, CL2P/725

14-12 AWG: FPLP, CL3P

Applicable Standards

UL Type	CMP, CL3P, FPLP
ROHS Compliant	Yes

Electricals

Voltage Rating	300 V
Temperature Rating	-4°C to 75°C
Conductors	ASTM B-3, B-8
Capacitance	52 pF/ft

Print Legend

COMMODITY CABLES, INC. 18 AWG 3C SHLD (UL) TYPE CL3P/FPLP OR c(UL)us TYPE CMP E498766 A1001.

Made in USA

Toll Free: (866) 945-5051

Local: (770) 945-5051

Fax: (770) 945-9582

www.commoditycables.com

Construction Details

Total Number Conductors	3
AWG	18
Stranding	Stranded
Conductor Material	Bare copper
Insulation Material	Low smoke copolymer
Insulation Thickness	.009"
Nominal Insulation Diameter	.064"
Color Code	Black, Red, White
Drain wire	24 AWG 7/32 tinned copper
Cabling Overall Lay	3" left hand lay
Tape Material	Aluminium Mylar
Final Jacket Material	Low smoke copolymer
Nominal Thickness	.015"
Jacket Color	White, Gray
Nominal Jacket Diameter	.172"
Ripcord	Yes

Print (Surface Print)

Inkjet	Yes
Sequential Foot Marks	Yes

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.



All values in this specification are nominal and are subject to tolerances of +/- 10 to 15%. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice