



www.commoditycables.com

PART NO. 2206SCMRBG



Description

22 AWG Bare copper 6 Conductor Shielded riser rated gray jacket

Features and Benefits

RoHS Compliant

Cables are manufactured to meet current NEC guidelines and are verified by outside standards organizations including c(UL)us and c(ETL)us.

Footage marked descending.

Suitable Application

- Security Systems
- Sound/Audio System
- Intercom Systems
- Power-Limited Controls

Standards

NEC Articles

22-16 AWG: FPLR/760, CMR/800, CL3R, CL2R/725

14-12 AWG: FPLR, CL3R

Applicable Standards

UL Type	CMR, CL2R, CL3R, FPLR
ROHS Compliant	Yes

Electricals

Operating Voltage	300 Volts
Capacitance CDR	29.60 pF/ft
Temperature Rating	-20C to + 75C
Conductors	ASTM B-3, & B-8

Print Legend

COMMODITY CABLES, INC. 22 AWG 6C SHIELDED (UL) TYPE CL3R/FPLR OR c(UL)us TYPE CMR E498766 A1001. Made in USA

Toll Free: (866) 945-5051

Local: (770) 945-5051

Fax: (770) 945-9582

www.commoditycables.com



Construction Details

Total Number Conductors	6
AWG	22
Stranding	7 Strand
Conductor Material	Bare copper
Insulation Material	Polyvinylchloride
Insulation Thickness	.010"
Nominal Insulation Diameter	.050"
Color Code	Black, Red, White, Green
Cabling Overall Lay	2 1/2" left hand lay
Tape Material	Aluminium Mylar
Drain Wire Material	24 AWG 7 Strand Tinned Copper
Final Jacket Material	Polyvinylchloride
Nominal Thickness	.015"
Jacket Color	Gray
Nominal Jacket Diameter	.166"
Ripcord	Yes

Print (Surface Print)

Inkjet	Yes
Sequential Foot Marks	Yes

Preparation for Shipment

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available. Shipping containers shall be constructed as to eliminate any possible damage to the cables due to shipment.

All values in this specification are nominal and are subject to tolerances of +/- 10 to 15%. It is the sole responsibility of the user to have the most current specification. Specifications are subject to change without notice